



# Rustic TopOil

## GENERAL DESCRIPTION

A surface maintainer for use on floors which have been treated with Junckers Rustic Oil or Hardwax Oil.

TopOil is easy to apply and fast drying so the floor is ready for use after 30 to 60 minutes.

TopOil protects the surface, restores a uniform sheen to the floor and reduces the effects of scratches and abrasions.

### Junckers Rustic TopOil is Indoor Climate Certified

An Indoor Climate Certified product has undergone extensive degassing and odour tests. This ensures that there are no chemical substances in the product, which adversely affect the air quality in the room.

For professional and private use.

---

## PRODUCT DESCRIPTION

### Product:

Waterbased air-drying alkyd oil

### Package sizes:

Ultra matt: 1 liter., 2.5 liter., 10 litre

Silk matt: 1 liter., 2.5 liter., 10 litre

### Appearance:

Dries to colourless ultra matt appearance.

---

---

**TECHNICAL DATA**

**Coverage:** 30-50 m<sup>2</sup> per litre.

**Before application:** Shake/stir well before use.

**Application tools:**

Flat floor mop or cotton cloth.

**Substrate temperature:** Minimum 15° C.

**Dilution:** Delivered ready for use. Dilution is not recommended.

**Drying time at 20° C and 50 % RH :**

Ready for light traffic after 30-60 minutes at 20° C and 50 % RH. Fully cured after 24 hours.

**Cleaning of tools:** Soap and water immediately after use

**Storage:** Lasts for 2 years if unopened and stored at 20° C. Not to be exposed to temperatures below 0° C.

---

**SYSTEM RECOMMENDATIONS**

**All areas:**

1 x Junckers Rustic TopOil  
+ 30-60 minutes drying time

The frequency of treatment varies with the amount of traffic on the floor. The more traffic the higher the frequency of the treatment.

---

## DIRECTION FOR USE

The oiled surface must be absolutely clean, dry and free from dust, grease, polish and detergent residue.

Dirt and irregularities can be removed by Junckers Neutralizer, sanding with fine-grained sandpaper, 180-240 grit, or a polishing machine equipped with a corresponding pad. Remove sanding dust with a vacuum cleaner.

It is important to ensure that the priming oil is intact and is one of Junckers oils before applying Junckers Rustic Top Oil.

Apply an even thin layer. Please note that the oil hardens quickly so care should be taken to spread and work the oil before it dries. Keep any overlaps with dry areas to a minimum. If there are blotches after application, polish these when dry with a green scrubbing sponge or on more extensive areas with a green pad, or a polishing machine with a polishing disc.

### Spot repairs

Floors regularly maintained with Junckers Rustic Top Oil can be spot repaired in walking lanes and other areas with high traffic.

### Surfaces worn through:

If the surface is not sound and stable the floor must first be sanded followed by application of one of Junckers priming oils.

---

## PRECAUTIONARY MEASURES

Before using the product, read the label on the container carefully and observe the recommended precautionary measures.

See Material Safety Data Sheet for detailed information.

---

## FURTHER INFORMATION

### Products:

F 2.1 - Junckers Rustic Oil

F 2.4 - Junckers Rustic Solid 100 Oil

F 3.4 - Junckers Professional HardWax Oil

F 10.3 - Junckers SylvaNeutralizer