



Easy and fast drying solution to filling of gaps from knots and cracks in all kinds of interior wood.
Nem og hurtigtørrende løsning til udfyldning af huller fra knaster og revner i alle former for træværk indendørs

Filler Powder

GENERAL DESCRIPTION

Junckers Filler Powder mixed with water provides an easy and fast drying solution to filling of gaps from knots and cracks in all kinds of interior wood.

Junckers Filler Powder is supplied in a colour assortment for most types of wood.

After curing Junckers Filler Powder can be sanded and sealed using the same procedures as for natural wood.

For private and professional use.

PRODUCT DESCRIPTION

Product:

Inorganic, coloured powder to be mixed with water before use.

Package sizes:

100 grams

TECHNICAL DATA

Mixing: 2 parts of Junckers Filler Powder to 1 part of hot water.

Application tools:
Spatula

Substrate temperature: Above 15° C.

Drying time at 20° C and 50 % RH :
Approx. 4 hours at room temperature.
Maximum hardness is achieved after 24 hours.

Cleaning of tools: Soapy water before the mixed material is dry. Dried material is removed by scraping or sanding.

Storage: Lasts for 2 years if unopened and stored at 20° C. Exposure to moisture will convert the powder to a solid insoluble material.

DIRECTION FOR USE

Application:
Mix Junckers Filler Powder with water in the recommended mixing proportions and apply with a spatula in necessary amounts.

Surplus material is easily removed with a damp cloth before complete drying.

Sanding: If sanding is required use the same grit of sandpaper as for the wood.

PRECAUTIONARY MEASURES

Before using the product, read the label on the container carefully and observe the recommended precautionary measures.

See Material Safety Data Sheet for detailed information.
