

PROFESSIONAL HARDWAX OIL

PRODUCT INFORMATION



GENERAL DESCRIPTION

An incredibly durable and fast drying oil for sanded or untreated wooden floors.

Professional Hardwax Oil gives the floor a deep lustre and rich colour and is perfect for residential or commercial areas.

It is also ideal for use in locations where minimum closure time is important.

The product can be used for both priming and for final polishing coats. An additional coat may be required on porous timbers.

Professional Hardwax Oil cannot be overcoated with water-based lacquers.

For professional use only.

PRODUCT DESCRIPTION

Product: Hard wax and drying oil in solvents.

Package sizes: 5 litres.

Appearance: Haze light brown liquid. Clear when dry.

Gloss level: Matt to ultramatt.

TECHNICAL DATA

Coverage: 20-30 m² per litre.

Before application: Shake/stir well before use.

Application tools: Stainless steel spatula, roller or brush.
Depending on gloss level, a white or red pad for polishing.

Substrate temperature: Minimum 15 °C.

Dilution: Delivered ready for use.

Drying time at 20 °C and 50 % RH:

Recoating approx. 6 hours.

Fully cured after 6 days.

Cleaning of tools: Soap and water immediately after use.

Storage: Lasts for 2 years if unopened and stored at 20 °C. Once opened the product will start to form a skin and may harden in the can.

DIRECTION FOR USE

Untreated/sanded floors:

Ensure that the surface is absolutely clean, dry and free from dust, wax, grease, polish etc. Unevenness, dirt and discolouration can be removed by sanding in direction of the grain. Final sanding must be with sandpaper grit 100-120. Vacuum sanding dust.

- Apply Professional Hardwax Oil in an even coat with a roller or brush.
- Remove surplus material using a buffing machine and a soft cloth or pad.
- After minimum 6 hours, apply another coat of oil and repeat buffing.
- If the floor is not saturated after this treatment, then repeat.
- To increase gloss, buff using white pad after a minimum of 16 hours.

Regular cleaning:

Sweep or vacuum, and when necessary wipe with a well wrung out mop or cloth. To help removal of dirt from the surface a solution of SylvaCleaner can be added to the cleaning water.

Maintenance:

If the existing oil surface is sound and stable, the floor can be refreshed with Rustic Top Oil.

For worn through surfaces use Professional Hardwax Oil to restore the surface.

Sand or scour the surface carefully with fine sandpaper grit 180-220 or a green or black nylon pad and apply as described under "Untreated/sanded floors".

PRECAUTIONARY MEASURES

Before using the product, read the label on the container carefully and observe the recommended precautionary measures.

See Material Safety Data Sheet for detailed information.

FURTHER INFORMATION

Products:

F 2.7 - Junckers Rustic Top Oil

F 10.2 - Junckers SylvaCleaner