

PROFESSIONAL HARDWAX OIL PRODUCT INFORMATION



GENERAL DESCRIPTION

An incredibly durable and fast drying indoor oil for sanded or untreated wooden floors.

Professional Hardwax Oil gives the floor a deep lustre and rich colour and is perfect for residential or commercial areas. It is also ideal for use in locations where minimum closure time is important.

The product can be used for both priming and for final polishing coats. Professional Hardwax Oil cannot be overcoated with water-based lacquers.

For professional use only.

PRODUCT DESCRIPTION

Product: Drying oil in solvents added wax.

Package size: 5 litres.

Appearance: Light brown liquid. Clear when dry.

Gloss level: Matt to ultramatt.

Risk of self-ignition: Cloths etc. used to apply the product can self-ignite. Place used cloths in an airtight and non-flammable container (e.g. a jam jar or a metal can with a lid). Dispose of in accordance with national waste regulations.

TECHNICAL DATA

Coverage: 20-30 m² per litre.

Before application: Shake/stir well before use.

Application tools: Stainless steel spatula, roller or brush.
Depending on gloss level, a white or red pad for polishing.

Substrate temperature: Minimum 15 °C.

Dilution: Delivered ready for use. Dilution is not recommended.

Drying time at 20 °C and 50 % RH:

Recoating approx. 6 hours.

Fully cured after 6 days.

Do not cover the surface by i.e. carpets or rugs before the oil is fully cured.

Cleaning of tools: Soap and water immediately after use.

Storage: Lasts for 2 years if unopened and stored at 20 °C. Once opened the product will start to form a skin and may harden in the can.

DIRECTIONS FOR USE

Untreated/sanded floors:

Ensure that the surface is absolutely clean, dry and free from dust, wax, grease, polish etc. Unevenness, dirt and discolouration can be removed by sanding in direction of the grain. Final sanding must be with sandpaper grit 100-120. Vacuum sanding dust.

- Apply the oil in an even coat until the surface is completely saturated.
- Make sure that the oil appears glossy/wet and spread the oil from wet to dry areas, where the oil has been absorbed.
- Remove surplus material using a buffing machine and a soft cloth or pad.
- After minimum 6 hours, apply another coat of oil and repeat buffing.
- To increase gloss, buff using white pad after a minimum of 16 hours.

Regular cleaning:

Sweep or vacuum, and when necessary wipe with a well wrung out flat mop or cloth. To help removal of dirt from the surface Junckers SylvaCleaner can be added to the cleaning water.

Maintenance:

If the existing oil surface is sound and stable, the floor can be refreshed with Junckers Rustic Top Oil.

For worn through surfaces use Professional Hardwax Oil to restore the surface.

Sand or scour the surface carefully with fine sandpaper grit 180-220 or a green or black nylon pad and apply as described under "Untreated/sanded floors".

PRECAUTIONARY MEASURES

Before using the product, read the label on the container carefully and observe the recommended precautionary measures.

See Material Safety Data Sheet for detailed information.

FURTHER INFORMATION

Products:

F 2.7 - Junckers Rustic Top Oil

F 10.2 - Junckers SylvaCleaner

Manufacturer:

Junckers Industrier A/S
www.junckers.com

Denmark: +45 70 80 30 00 / teknik@junckers.com
ExportDept.: +45 70 80 30 00 / export@junckers.com

Junckers Ltd. +44 1376 534700 / tech@junckers.co.uk
Junckers Hardwood (USA) +1 800 878-9663 / info@junckershardwood.com
Junckers France S.A. +33 5 5944 8518 / commercial@junckers-france.fr
Junckers Iberica S.A. +34 915 075 719 / info@junckers.es
Junckers S.r.l. +39 348 4405255 / info@junckers.it
Junckers Parkett GmbH. +49 0351-84387077 / info@junckers.de

F 3.4
2021-07-13
Replacement Of
2020-09-17