

SAFETY DATA SHEET

SB FILLER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

SB FILLER

Unique formula identifier (UFI)

QM00-Y02Y-T00H-F6WW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Filling of wood.

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Junckers Industrier A/S

Vaerftsvej 4

4600 Koege

Denmark

Tel. +45 70 80 30 00

E-mail

productsafety@junckers.dk

Revision

17/03/2023

SDS Version

1.0

1.4. Emergency telephone number

The National Poisons Information Centre (NPIC)

Public: +353 (0) 1 809 2166 (7 days a week, 8am- 10pm)

Healthcare professionals: +353 (0) 1 809 2566 (24 h service)

See also section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Highly flammable liquid and vapour. (H225)

Causes serious eye irritation. (H319)

May cause drowsiness or dizziness. (H336)

Safety statement(s)

General

-

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
 Avoid breathing vapour. (P261)
 Wear eye protection/protective gloves. (P280)

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing. (P305+P351+P338)
 If eye irritation persists: Get medical advice/attention. (P337+P313)

Storage

Store in a well-ventilated place. Keep container tightly closed. (P403+P233)

Disposal

-

Hazardous substances

Acetone

Additional labelling

EUH066, Repeated exposure may cause skin dryness or cracking.
 UFI: QM00-Y02Y-T00H-F6WW

2.3. Other hazards

Additional warnings

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Acetone	CAS No.: 67-64-1 EC No.: 200-662-2 REACH: 01-2119471330-49 Index No.: 606-001-00-8	60-80%	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
n-Butyl acetate	CAS No.: 123-86-4 EC No.: 204-658-1 REACH: 01-2119485493-29 Index No.: 607-025-00-1	3-5%	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336	[1]
Ethanol	CAS No.: 64-17-5 EC No.: 200-578-6 REACH: 01-2119457610-43 Index No.: 603-002-00-5	3-5%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 (SCL: 50.00 %)	
Propan-2-ol	CAS No.: 67-63-0 EC No.: 200-661-7 REACH: 01-2119457558-25 Index No.: 603-117-00-0	1-3%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.
 Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an

unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact the National Poisons Information Centre (NPIC) on +353 (0) 1 809 256 (24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the

regulations on dangerous waste.

Use sand, sawdust, soil, vermiculite or similar to collect liquid material. Subsequently, place in a suitable waste container.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

Store in cool, dry conditions in well sealed receptacles.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Acetone

Long term exposure limit (8 hours) (mg/m³): 1210

Long term exposure limit (8 hours) (ppm): 500

Annotations:

IOELV = Indicative Occupational Exposure Limit Values are health based limits set under the Chemical Agents Directive (98/24/EC).

n-Butyl acetate

Long term exposure limit (8 hours) (mg/m³): 241

Long term exposure limit (8 hours) (ppm): 50

Short term exposure limit (15 minutes) (mg/m³): 723

Short term exposure limit (15 minutes) (ppm): 150

Annotations:

IOELV = Indicative Occupational Exposure Limit Values are health based limits set under the Chemical Agents Directive (98/24/EC).

Ethanol

Short term exposure limit (15 minutes) (ppm): 1000

Propan-2-ol

Long term exposure limit (8 hours) (ppm): 200

Short term exposure limit (15 minutes) (ppm): 400

Annotations:

Sk = Substance, which have the capacity to penetrate intact skin when they come in contact with it, and be absorbed into the body.

2021 Code of Practice for the Safety, Health and Welfare at Work (Chemical Agents) Regulations (2001-2015) and the Safety, Health and Welfare at Work (Carcinogens) Regulations (2001-2019).

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

DNEL

Acetone

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	62 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	186 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	200 mg/m ³
Long term – Systemic effects - Workers	Inhalation	1210 mg/m ³
Short term – Local effects - Workers	Inhalation	2420 mg/m ³
Long term – Systemic effects - General population	Oral	62 mg/kg bw/day

Ethanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	206 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	343 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	114 mg/m ³
Long term – Systemic effects - Workers	Inhalation	950 mg/m ³
Long term – Systemic effects - General population	Oral	87 mg/kg bw/day

n-Butyl acetate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	6 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	11 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	6 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	11 mg/kg bw/day
Long term – Local effects - General population	Inhalation	35,7 mg/m ³
Long term – Local effects - Workers	Inhalation	300 mg/m ³
Long term – Systemic effects - General population	Inhalation	35,7 mg/m ³
Long term – Systemic effects - Workers	Inhalation	300 mg/m ³
Short term – Local effects - General population	Inhalation	300 mg/m ³
Short term – Local effects - Workers	Inhalation	600 mg/m ³
Short term – Systemic effects - General population	Inhalation	300 mg/m ³
Short term – Systemic effects - Workers	Inhalation	600 mg/m ³
Long term – Systemic effects - General population	Oral	2 mg/kg bw/day
Short term – Systemic effects - General population	Oral	2 mg/kg bw/day

Propan-2-ol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	319 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	888 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	89 mg/m ³
Long term – Systemic effects - Workers	Inhalation	500 mg/m ³
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day

PNEC

Acetone

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		10,6 mg/l
Freshwater sediment		30,4 mg/kg dw

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Intermittent release (freshwater)		21 mg/l
Marine water		1,06 mg/l
Marine water sediment		3,04 mg/kg dw
Sewage treatment plant		100 mg/l
Soil		29,5 mg/kg dw
Ethanol		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0,96 mg/l
Freshwater sediment		3,6 mg/kg dw
Intermittent release (freshwater)		2,75 mg/l
Marine water		0,79 mg/l
Marine water sediment		2,9 mg/kg dw
Predators		0,38 g/kg
Sewage treatment plant		580 mg/l
Soil		0,63 mg/kg dw
n-Butyl acetate		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		0,18 mg/l
Freshwater sediment		0,981 mg/kg dw
Intermittent release (freshwater)		0,36 mg/l
Marine water		0,018 mg/l
Marine water sediment		0,098 mg/kg dw
Sewage treatment plant		35,6 mg/l
Soil		0,09 mg/kg dw
Propan-2-ol		
Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140,9 mg/l
Freshwater sediment		552 mg/kg dw
Intermittent release (freshwater)		140,9 mg/l
Marine water		140,9 mg/l
Marine water sediment		552 mg/kg dw
Predators		160 mg/kg
Sewage treatment plant		2251 mg/l
Soil		28 mg/kg dw

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Hygiene measures

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure


No specific requirements.

Individual protection measures, such as personal protective equipment


Generally

Use only CE marked protective equipment.


Respiratory Equipment

Type	Class	Colour	Standards	
Gas filter AX	-	Brown	EN14387	


Skin protection

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn	-	-	

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Butyl	0,3	> 480	EN374-2, EN374-3, EN388	

Eye protection

Type	Standards	
Safety glasses with side shields	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Liquid

Colour

Clear

Odour / Odour threshold

Acetone

pH

Testing not relevant or not possible due to the nature of the product.

Density (g/cm³)

0,85

Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

Particle characteristics

Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

Softening point/range (waxes and pastes) (°C)

Does not apply to liquids.

Boiling point (°C)

56

Vapour pressure

Testing not relevant or not possible due to the nature of the product.

Relative vapour density

Testing not relevant or not possible due to the nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Data on fire and explosion hazards

Flash point (°C)

-18

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Soluble

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

Not applicable.

Other information

Propan-2-ol has been classified by IARC as a group 3 carcinogen.

SECTION 12: Ecological information

12.1. Toxicity

No data available.

12.2. Persistence and degradability

Product/substance	Acetone
Biodegradable:	Yes
Test method:	OECD 301 B
Result:	90 %

Product/substance	n-Butyl acetate
Biodegradable:	Yes
Test method:	OECD 301 D
Result:	83 %

Product/substance	Ethanol
Biodegradable:	Yes
Test method:	OECD 301 B
Result:	> 60 %

Product/substance	Propan-2-ol
Biodegradable:	Yes
Test method:	BOD5/COD
Result:	0,5

12.3. Bioaccumulative potential

Product/substance	Acetone
Test method:	
Potential bioaccumulation:	No
LogPow:	-0,24
BCF:	3
Other information:	

Product/substance	n-Butyl acetate
Test method:	
Potential bioaccumulation:	No
LogPow:	2,3
BCF:	15
Other information:	

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

Product/substance Ethanol
 Test method:
 Potential bioaccumulation: No
 LogPow: -0,35
 BCF: No data available.
 Other information:

Product/substance Propan-2-ol
 Test method:
 Potential bioaccumulation: No
 LogPow: 0,05
 BCF: 3.2
 Other information:

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste.
 HP 3 - Flammable
 HP 4 - Irritant (skin irritation and eye damage)
 Dispose of contents/container to an approved waste disposal plant.
 Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

08 04 09* Waste adhesives and sealants containing organic solvents or other dangerous substances



Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es) Labels: 3 Classification code: F1	14.4 PG*	14.5 Env**	Other information:
ADR	UN1263	PAINT	Class: 3 Labels: 3 Classification code: F1 	II	No	Limited quantities: 5 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1263	PAINT	Class: 3 Labels: 3 Classification code: F1 	II	No	Limited quantities: 5 L EmS: F-E S-E See below for additional information.

According to EC-Regulation 1907/2006 (REACH), annex II, including changes implemented by EC-Regulation 2020/878

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
IATA	UN1263	PAINT	Class: 3 Labels: 3 Classification code: F1 	II	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements.

SEVESO - Categories / dangerous substances

P5c - FLAMMABLE LIQUIDS, Qualifying quantity (lower-tier): 5.000 tonnes / (upper-tier): 50.000 tonnes

Regulation on drug precursors

Acetone is included (Category 3)

Additional information

Not applicable.

Sources

Maternity Protection Act 1994 (34/1994) with later amendments.

SI No 209 of 2015 Chemicals Act (Control of Major Accident Hazards involving Dangerous Substances) Regulations 2015.

Commission Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

Council Regulation (EC) No 273/2004 on drug precursors.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (CLP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH = CLP-specific hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of classification and labelling of chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = Logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = Specific Concentration Limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time Weighted Average

UN = United Nations

UVCB = Substances of Unknown or Variable composition, Complex reaction products or Biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and very Bioaccumulative

Additional information

The classification of the mixture in regard of health hazards is in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP).

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

ULS

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: IE-en